

**GO-GO**<sup>®</sup>  
ELITE TRAVELLER PLUS<sup>®</sup>

THE QUICKEST WAY  
TO TRAVEL.

## GO-GO ELITE TRAVELLER<sup>®</sup> PLUS

The **Go-Go Elite Traveller<sup>®</sup> Plus** was designed to bring travel scooters to a greater range of people than ever before. An increase in length and width, and a weight capacity of 147 kg (23 Stone 3 lbs.) combine with wraparound delta tiller to allow both the larger individual and those with limited dexterity to experience the benefits of a specific travel mobility product for the first time. Feather-touch disassembly makes the Go-Go Elite Traveller Plus the easiest travel scooter to take along anywhere.



(Images are for illustration purposes only)

(Tel) 01869 324 600 • (Fax) 01869 323 070 • [www.pridemobility.co.uk](http://www.pridemobility.co.uk)

**Pride<sup>®</sup>**  
Mobility Products Ltd.  
— LIVE YOUR BEST<sup>®</sup> —

Go-Go Elite Traveller® Plus	3-wheel	4-wheel
Weight capacity:	147 kg (23 Stone 3 lbs.)	147 kg (23 Stone 3 lbs.)
Maximum speed <sup>1</sup> :	Up to 6.4 km/h (4 mph)	Up to 6.4 km/h (4 mph)
Ground clearance <sup>2</sup> :	7.62 cm (3") at midframe	7.62 cm (3") at midframe
Turning radius <sup>2</sup> :	87.6 cm (34.5")	116.2 cm (45.75")
Overall length <sup>2</sup> :	101.6 cm (40")	102.25 cm (40.25")
Overall width <sup>2</sup> :	53.7 cm (21.2")	53.7 cm (21.2")
Tyre size:		
Front:	5 cm x 20.32 cm (2" x 8") solid	5 cm x 20.32 cm (2" x 8") solid
Rear:	7.62 cm x 22.86 cm (3" x 9") solid	7.62 cm x 22.86 cm (3" x 9") solid
Maximum allowable incline:	10.5% (6°)	10.5% (6°)
Maximum angle capacity:	17.6% (10°)	17.6% (10°)
Maximum obstacle climbing ability:	6.5 cm (2.5")	6.5 cm (2.5")
Total weight w/o battery pack <sup>4</sup> :	39 kg (86 lbs.)	39.2 kg (86.5 lbs.)
Heaviest piece when disassembled:	14.7 kg (32.5 lbs.) (front section)	16 kg (35 lbs.) (front section)
Drive system:	24-volt DC motor, sealed mini-transaxle	
Dual braking system:	Electronic, regenerative, and electromechanical	
Standard seating:	Type: Foldable Weight: 10.2 kg (22.5 lbs.) Material: Black vinyl Dimensions: 43.18 cm (17") overall width 43.18 cm (17") effective depth	
Battery requirements <sup>3</sup> :	Two 12-volt, deep cycle (standard) Size: 2 x 17 AH (standard) Weight <sup>5</sup> : 17 AH: 13.4 kg (29.5 lbs.) battery pack	
Battery charger:	Off-board, 2-amp	

Standard colours:



Blue



Red

2 sets of exciting colours with every scooter!

## Features

- Feather-touch disassembly with one hand
- Exclusive black, low-profile, non-scaffing tyres with new tri-spoke mags
- Delta tiller with wraparound handles
- 23 cm (9") rear wheels
- 147 kg (23 Stone 3 lbs.) weight capacity
- Auto-connecting front to rear cable
- Includes 2 sets of easily changeable coloured panels - Red and Blue
- Front frame-mounted seat post offers maximum stability
- All new frame design easily disassembles into 5 super lightweight pieces for convenient transport and storage
- Modular design for easy serviceability
- Microprocessor-based controller offers optimal power management and added safety features
- Front tiller-mounted basket
- Removable footboard basket for additional storage (4-wheel version only)
- Convenient off-board dual voltage charger can charge battery pack on-board or off-board

## Options

- Cup holder
- Rear basket
- Crutch holder



Feather-touch disassembly

<sup>1</sup> Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition. This specification can be subject to a variance of + 10%, -5%.

<sup>2</sup> Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).

<sup>3</sup> AGM or gel cell type required.

<sup>4</sup> Includes standard seat.

<sup>5</sup> Battery weight may vary based on manufacturer.

The information contained herein is correct at the time of publication; due to the manufacturer's commitment to constant improvement and development, they reserve the right to alter specifications without prior notice.

NOTE: This product conforms to all applicable ANSI/RESNA testing requirements and ISO 7176 series EN12184 standards. All specifications subject to change without notice.

32 Wedgwood Road, Bicester, Oxfordshire OX26 4UL

(Tel) 01869 324 600 • (Fax) 01869 323 070 • [www.pridemobility.co.uk](http://www.pridemobility.co.uk)